

2-POSITION COAXIAL ANTENNA SWITCH



SPECIFICATIONS	AV-SW2M	AV-SW2N
FREQUENCY RANGE	DC-1GHz	DC-3GHz
POWER RANGE DC ~ 30MHz 30MHz ~ 200MHz 200MHz ~ 500MHz 500MHz ~ 1GHz 1GHz ~ 3GHz	2KW 1KW 500W 250W	2KW 1KW 500W 250W 150W
INSERTION LOSS DC ~ 500MHz 500MHz ~ 1GHz 1GHz ~ 2GHz 2GHz ~ 3GHz	≥0.05dB ≥0.10dB	≥0.05dB ≥0.10dB ≥0.15dB ≥0.20dB
ISOLATION DC ~ 500MHz 500MHz ~ 1GHz 1GHz ~ 2GHz 2GHz ~ 3GHz	≥70.0dB ≥60.0dB	≥70.0dB ≥60.0dB ≥55.0dB ≥50.0dB
VSWR DC ~ 500MHz 500MHz ~ 1GHz 1GHz ~ 2GHz 2GHz ~ 3GHz	≥1.05 ≥1.15	≥1.05 ≥1.10 ≥1.15 ≥1.25
PACKAGING	Blister Packing	