

Fireco masts

Electropneumatic mast

Roof Base Pro / Roof Plus Pro

Roof Base Pro Zero - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.5511.N	N	2	64mm	1.734	1.264	15	49	150
RE.5512.N	N	2	64mm	2.219	1.52	15	51	130

Roof Base Pro Ultralight - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.5611.N	N	3	77mm	2.068	1.255	15	51.0	160
RE.5612.N	N	3	77mm	2.503	1.368	15	52.0	140
RE.5613.N	N	3	77mm	2.99	1.563	15	53.5	125
RE.5514.N	N	3	77mm	3.118	1.596	15	54.0	120

Roof Plus Pro Light - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.5711.N	N	3	90mm	2.475	1.437	25	63.0	145
RE.5712.N	N	3	90mm	2.815	1.572	25	64.0	135
RE.5713.N	N	3	90mm	3.115	1.672	20	65.0	125
RE.5714.N	N	3	90mm	3.415	1.772	20	66.0	115

Roof Plus Pro Standard - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.5811.N	N	4	115mm	3.101	1.531	30	68.0	160
RE.5812.N	N	4	115mm	3.467	1.605	30	69.5	150
RE.5813.N	N	4	115mm	3.867	1.705	25	71.0	140
RE.5814.N	N	4	115mm	4.253	1.818	25	72.5	130



Code N: Non-turnable mast

Code T: Manually turnable mast 360°

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information