

Fireco masts

Pneumatic mast Roof mount

Roof ECO - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.4401.N	N	1	77mm	1.45	25	6.0	110
RE.4402.N	N	1	77mm	1.75	25	6.5	110
RE.4403.T	T	1	77mm	1.485	25	7.5	110
RE.4404.T	T	1	77mm	1.785	25	8.0	110

Roof Entry - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.4301.N	N	2	66mm	2.0	1.2	15	7.0	100
RE.4302.N	N	2	66mm	2.5	1.45	15	8.0	100
RE.4303.N	N	2	66mm	3.0	1.7	15	9.0	100

Roof Entry - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.4331.N	N	3	66mm	2.5	1.135	15	10.0	100
RE.4332.N	N	3	66mm	3.0	1.3	15	11.0	100
RE.4333.N	N	3	66mm	3.5	1.47	15	12.0	100



Code N: Non-turnable mast

Code T: Manually turnable mast 360°

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast Roof mount

Roof ECO Zero - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.4311.N	N	2	64mm	1.8	1.1	20	10.0	100
RE.4312.N	N	2	64mm	2.4	1.4	20	11.0	100
RE.4313.T	T	2	64mm	1.835	1.135	20	11.0	100
RE.4314.T	T	2	64mm	2.435	1.435	20	12.0	100

Roof ECO Zero - internal spiralled cable - CONTINUED

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.4321.N	N	3	64mm	2.4	1.1	20	12.0	100
RE.4322.N	N	3	64mm	3.0	1.4	20	13.0	100
RE.4323.T	T	3	64mm	2.435	1.135	20	13.0	100
RE.4324.T	T	3	64mm	1.135	1.135	20	14.0	100

Roof ECO Ultralight - internal spiralled cable

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.4411.N	N	2	77mm	2.0	1.2	25	12.0	100
RE.4412.N	N	2	77mm	2.5	1.45	25	13.0	100
RE.4413.T	T	2	77mm	2.035	1.235	25	13.0	100
RE.4414.T	T	2	77mm	2.535	1.485	25	14.0	100

Roof ECO Ultralight - internal spiralled cable - CONTINUED

P/N	Code	Sections	Diameter	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
RE.4421.N	N	3	77mm	2.5	1.135	25	13.0	100
RE.4422.N	N	3	77mm	3.2	1.38	25	14.0	100
RE.4423.T	T	3	77mm	2.535	1.17	25	14.0	100
RE.4424.T	T	3	77mm	3.235	1.415	25	15.0	100



Code N: Non-turnable mast

Code T: Manually turnable mast 360°

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information