

Fireco masts

Pneumatic mast

Hand-pump or compressed air

Zero - Small mast

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CZ.3301.N	N	64mm	3	1.855	0.939	20	6.4	160
CZ.3302.N	N	64mm	3	2.251	1.069	20	7.0	150
CZ.3303.N	N	64mm	3	2.74	1.234	20	7.6	140
CZ.3304.N	N	64mm	3	3.151	1.369	20	8.2	150
CZ.3305.N	N	64mm	3	3.651	1.539	20	8.9	140
CZ.3306.N	N	64mm	3	4.125	1.709	15	9.5	130
CZ.3307.N	N	64mm	3	4.635	1.879	15	10.2	145
CZ.3308.N	N	64mm	3	5.145	2.049	15	11.0	135
CZ.3309.N	N	64mm	3	5.561	2.219	15	11.7	125
CZ.3301.T	T	64mm	3	1.9	0.984	20	8.2	160
CZ.3301.T	T	64mm	3	2.296	1.114	20	8.8	150
CZ.3301.T	T	64mm	3	2.785	1.279	20	9.4	140
CZ.3301.T	T	64mm	3	3.196	1.414	20	10.0	150
CZ.3301.T	T	64mm	3	3.969	1.584	20	10.7	140
CZ.3301.T	T	64mm	3	4.170	1.754	15	11.4	130
CZ.3301.T	T	64mm	3	4.68	1.924	15	12.1	145
CZ.3301.T	T	64mm	3	5.19	2.094	15	12.8	135
CZ.3301.T	T	64mm	3	5.696	2.264	15	13.5	125

Code N: Non-turnable mast

Code T: Manually turnable mast 360°



* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast

Hand-pump or compressed air

Ultralight - Small mast

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CU.3316.N	N	77mm	3	2.253	1.07	25	8.7	150
CU.3317.N	N	77mm	3	2.7	1.235	25	9.6	140
CU.3318.N	N	77mm	3	3.126	1.369	25	10.3	130
CU.3319.N	N	77mm	3	3.617	1.54	25	11.2	145
CU.3320.N	N	77mm	3	4.117	1.71	25	12.1	135
CU.3321.N	N	77mm	3	4.595	1.88	22	13.0	125
CU.3322.N	N	77mm	3	5.117	2.05	20	13.9	160
CU.3323.N	N	77mm	3	5.599	2.22	20	14.7	150
CU.3324.N	N	77mm	3	6.067	2.39	18	15.6	140
CU.3316.T	T	77mm	3	2.297	1.114	25	10.1	150
CU.3317.T	T	77mm	3	2.744	1.279	25	11.0	140
CU.3318.T	T	77mm	3	3.17	1.413	25	11.8	130
CU.3319.T	T	77mm	3	3.661	1.584	25	12.6	145
CU.3320.T	T	77mm	3	4.161	1.754	25	13.5	135
CU.3321.T	T	77mm	3	4.639	1.924	22	14.4	125
CU.3322.T	T	77mm	3	5.161	2.094	20	15.3	160
CU.3323.T	T	77mm	3	5.643	2.264	20	16.2	150
CU.3324.T	T	77mm	3	6.111	2.434	18	17.0	140

Code N: Non-turnable mast

Code T: Manually turnable mast 360°



* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast

Hand-pump or compressed air

Ultralight - Small mast - CONTINUED

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CU.3401.N	N	77mm	4	2.441	1.001	20	9.4	160
CU.3402.N	N	77mm	4	2.944	1.149	20	10.2	150
CU.3403.N	N	77mm	4	3.424	1.269	20	11.0	140
CU.3404.N	N	77mm	4	3.932	1.399	20	11.8	150
CU.3405.N	N	77mm	4	4.597	1.569	16	12.8	135
CU.3406.N	N	77mm	4	5.274	1.739	16	13.9	120
CU.3407.N	N	77mm	4	5.873	1.909	13	14.9	130
CU.3408.N	N	77mm	4	6.422	2.099	13	16.0	115
CU.3409.N	N	77mm	4	6.962	2.269	12	16.9	105
CU.3401.T	T	77mm	4	2.485	1.045	20	10.8	160
CU.3402.T	T	77mm	4	2.988	1.193	20	11.6	150
CU.3403.T	T	77mm	4	3.468	1.313	20	12.4	140
CU.3404.T	T	77mm	4	3.976	1.443	20	13.2	150
CU.3405.T	T	77mm	4	4.641	1.613	16	14.3	135
CU.3406.T	T	77mm	4	5.318	1.783	16	15.3	120
CU.3407.T	T	77mm	4	5.917	1.953	13	16.3	130
CU.3408.T	T	77mm	4	6.466	2.143	13	17.4	115
CU.3409.T	T	77mm	4	7.006	2.313	12	18.3	105

Code N: Non-turnable mast

Code T: Manually turnable mast 360°



* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information