

## Fireco masts

### Pneumatic mast

#### Hand-pump or compressed air

#### Star - without internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CA.5221	P or H	66mm	2	1.93	1.12	23	4.5	180
CA.5222	P or H	66mm	2	2.48	1.37	23	5.0	165
CA.5223	P or H	66mm	2	2.98	1.62	23	5.5	150
CA.5321	P or H	66mm	3	2.739	1.12	19	5.5	135
CA.5322	P or H	66mm	3	3.244	1.315	19	6.0	125
CA.5323	P or H	66mm	3	3.759	1.62	19	7.0	115
CA.5401	P or H	66mm	4	3.483	1.2	15	6.5	110
CA.5402	P or H	66mm	4	3.983	1.325	15	7.0	100
CA.5403	P or H	66mm	4	4.483	1.45	15	7.5	90
CA.5501	P or H	66mm	5	4.02	1.17	12	7.0	95
CA.5502	P or H	66mm	5	4.44	1.27	12	7.5	90
CA.5503	P or H	66mm	5	4.94	1.37	12	8.0	80

#### Primo - without internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CP5411	P or H	66mm	4	2.963	1.07	16	6.0	120
CP5412	P or H	66mm	4	3.483	1.2	15	6.5	110
CP5413	P or H	66mm	4	3.963	1.32	15	7.0	100
CP5414	P or H	66mm	4	4.483	1.45	14	7.5	90
CP5415	P or H	66mm	4	5.103	1.62	13	8.0	85
CP5416	P or H	66mm	4	5.923	1.81	12	9.0	75
CP5601	P or H	66mm	6	3.42	1.0	9	7.0	105
CP5602	P or H	66mm	6	3.93	1.085	9	7.5	95
CP5603	P or H	66mm	6	4.49	1.17	9	8.0	85
CP5604	P or H	66mm	6	5.23	1.335	8	8.5	75
CP5605	P or H	66mm	6	5.98	1.46	8	9.0	65
CP5606	P or H	66mm	6	7.016	1.616	7	10.0	110
CP5607	P or H	66mm	6	7.93	1.835	7	11.0	95
CP5608	P or H	66mm	6	9.08	1.96	6	11.5	80



\* denounces 1 level guy lines required, fitted to top section. \*\* denounces 2 levels of guy rings/lines required. \*\*\* denounces 3 levels of guy rings/lines required - consult ZCG for more information

## Fireco masts

### Pneumatic mast

#### Hand-pump or compressed air

#### Super Primo - without internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CO.5426	P or H	80mm	4	4.983	1.65	24	10.5	115
CO.5427	P or H	80mm	4	5.923	1.81	23	11.5	100
CO.5428	P or H	80mm	4	6.923	2.06	20	12.5	85
CO.5616	P or H	80mm	6	5.01	1.29	18	11.0	110
CO.5617	P or H	80mm	6	6.005	1.46	16	12.0	90
CO.5618	P or H	80mm	6	6.995	1.625	16	13.0	75
CO.5619	P or H	80mm	6	7.93	1.835	14	14.5	160
CO.5620*	P or H	80mm	6	8.87	1.95	13	15.0	150
CO.5621*	P or H	80mm	6	10.12	2.2	11	16.5	135
CO.5622*	P or H	80mm	6	10.97	2.55	10	19.0	120
CO.5623*	P or H	80mm	6	12.02	2.8	10	20.5	105
CO.5701	P or H	80mm	7	5.033	1.22	12	11.5	105
CO.5702	P or H	80mm	7	6.013	1.36	12	12.4	90
CO.5703	P or H	80mm	7	7.034	1.523	11	13.5	75
CO.5704*	P or H	80mm	7	8.023	1.69	9	14.8	155
CO.5705*	P or H	80mm	7	9.003	1.83	9	15.7	140
CO.5706*	P or H	80mm	7	10.018	1.975	8	16.7	125
CO.5707*	P or H	80mm	7	11.013	2.16	8	18.1	110
CO.5708*	P or H	80mm	7	12.028	2.305	7	19.1	95
CO.5709**	P or H	80mm	7	13.023	2.49	6	20.0	130
CO.5710**	P or H	80mm	7	14.003	2.63	5	20.8	115
CO.5711**	P or H	80mm	7	15.018	2.775	5	22.0	100
CO.5712**	P or H	80mm	7	16.663	3.07	4	24.0	80
CO.5801	P or H	80mm	8	5.799	1.2	9	11.6	90
CO.5802	P or H	80mm	8	6.999	1.42	9	13.4	70
CO.5803*	P or H	80mm	8	8.009	1.59	7	14.8	140
CO.5804*	P or H	80mm	8	9.011	1.715	7	15.7	125
CO.5805*	P or H	80mm	8	10.529	1.94	6	17.5	100
CO.5806*	P or H	80mm	8	11.979	2.13	6	18.9	80



\* denotes 1 level guy lines required, fitted to top section. \*\* denotes 2 levels of guy rings/lines required. \*\*\* denotes 3 levels of guy rings/lines required - consult ZCG for more information

## Fireco masts

### Pneumatic mast

#### Hand-pump or compressed air

#### Maxi Primo - without internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CM.5701	P or H	101mm	7	7.476	1.575	22	19.6	85
CM.5702	P or H	101mm	7	9.046	1.825	20	22.1	70
CM.5703	P or H	101mm	7	10.496	2.075	18	24.6	60
CM.5704*	P or H	101mm	7	12.476	2.375	12	27.5	120
CM.5705**	P or H	101mm	7	15.106	2.785	10	30.6	120
CM.5807	P or H	101mm	8	9.03	1.715	14	22.3	70
CM.5808	P or H	101mm	8	10.55	1.94	12	24.7	55
CM.5809*	P or H	101mm	8	12.0	2.13	11	26.7	115
CM.5810*	P or H	101mm	8	13.52	2.32	10	28.6	100
CM.5811**	P or H	101mm	8	14.96	2.5	9	30.5	120
CM.5812**	P or H	101mm	8	17.01	2.8	8	32.8	110
CM.5901	P or H	101mm	9	7.512	1.5	14	21.2	80
CM.5901	P or H	101mm	9	9.052	1.68	13	23.2	65
CM.5901	P or H	101mm	9	10.502	1.85	12	25.1	55
CM.5901	P or H	101mm	9	12.032	2.02	10	27.0	100
CM.5901*	P or H	101mm	9	13.492	2.2	9	29.0	90
CM.5901*	P or H	101mm	9	15.022	2.37	8	30.8	120
CM.5901**	P or H	101mm	9	16.860	2.592	7	32.5	110
CM.5901***	P or H	101mm	9	19.832	3.1	5	38.2	120
CM.5007	P or H	101mm	10	6.047	1.25	13	18.6	100
CM.5008	P or H	101mm	10	7.547	1.4	13	20.4	80
CM.5009*	P or H	101mm	10	8.867	1.55	11	22.2	130
CM.5010*	P or H	101mm	10	10.457	1.7	9	23.9	110
CM.5011*	P or H	101mm	10	11.957	1.85	8	25.6	90
CM.5012**	P or H	101mm	10	13.457	2.0	7	27.3	130
CM.5013**	P or H	101mm	10	14.597	2.15	5	29.2	120



\* denotes 1 level guy lines required, fitted to top section. \*\* denotes 2 levels of guy rings/lines required. \*\*\* denotes 3 levels of guy rings/lines required - consult ZCG for more information

## Fireco masts

### Pneumatic mast

#### Hand-pump or compressed air

#### Maxi Primo - without internal cable - CONTINUED

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CM.5101	P or H	101mm	7	7.476	1.575	22	19.6	85
CM.5102	P or H	101mm	7	9.046	1.825	20	22.1	70
CM.5103	P or H	101mm	7	10.496	2.075	18	24.6	60
CM.5104*	P or H	101mm	7	12.476	2.375	12	27.5	120
CM.5105*	P or H	101mm	7	15.106	2.785	10	30.6	120
CM.5106*	P or H	101mm	10	14.597	2.15	5	29.2	120



\* denotes 1 level guy lines required, fitted to top section. \*\* denotes 2 levels of guy rings/lines required. \*\*\* denotes 3 levels of guy rings/lines required - consult ZCG for more information