

Fireco masts

Pneumatic mast Steady Medium Masts

Light Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CL.6331.N	N	90mm	3	2.64	1.252	30	12.0	150
CL.6332.N	N	90mm	3	3.03	1.382	30	12.5	140
CL.6333.N	N	90mm	3	3.524	1.552	30	13.5	130
CL.6334.N	N	90mm	3	3.914	1.722	30	14.5	140
CL.6335.N	N	90mm	3	4.514	1.892	30	16.0	130
CL.6336.N	N	90mm	3	5.014	2.062	25	17.0	120
CL.6337.N	N	90mm	3	5.48	2.232	25	18.0	135
CL.6338.N	N	90mm	3	5.98	2.402	25	19.0	125
CL.6339.N	N	90mm	3	6.439	2.572	20	20.0	130
CL.6331.T	T	90mm	3	2.677	1.289	30	14.0	150
CL.6332.T	T	90mm	3	3.067	1.419	30	15.0	140
CL.6333.T	T	90mm	3	3.561	1.589	30	16.0	130
CL.6334.T	T	90mm	3	3.951	1.759	30	17.0	140
CL.6335.T	T	90mm	3	4.551	1.929	30	18.2	130
CL.6336.T	T	90mm	3	5.051	2.099	25	19.2	120
CL.6337.T	T	90mm	3	5.517	2.269	25	20.3	135
CL.6338.T	T	90mm	3	6.017	2.439	25	21.4	125
CL.6339.T	T	90mm	3	6.476	2.609	20	22.4	130



Code N: Non-turnable mast
Code T: Manually turnable mast 360°
Code R: Electric turning base 12/24V

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast

Steady Medium Masts

Light Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CL6416.N	N	90mm	4	2.298	1.019	30	11.5	145
CL6417.N	N	90mm	4	2.805	1.169	30	12.5	135
CL6418.N	N	90mm	4	3.273	1.289	30	13.5	125
CL6419.N	N	90mm	4	3.823	1.419	25	14.5	135
CL6420.N	N	90mm	4	4.492	1.589	25	16.0	120
CL6421.N	N	90mm	4	5.147	1.759	25	17.3	110
CL6422.N	N	90mm	4	5.767	1.929	22	18.5	120
CL6423.N	N	90mm	4	6.446	2.119	20	20.0	110
CL6424.N	N	90mm	4	6.946	2.274	18	21.0	100
CL6416.T	T	90mm	4	2.335	1.056	30	14.0	145
CL6417.T	T	90mm	4	2.842	1.206	30	15.0	135
CL6418.T	T	90mm	4	3.31	1.326	30	16.0	125
CL6419.T	T	90mm	4	3.86	1.456	25	1.0	135
CL6420.T	T	90mm	4	4.529	1.626	25	18.5	120
CL6421.T	T	90mm	4	5.184	1.796	25	19.5	110
CL6422.T	T	90mm	4	5.804	1.966	22	21.0	120
CL6423.T	T	90mm	4	6.483	2.156	20	22.3	110
CL6424.T	T	90mm	4	6.983	2.311	18	23.5	100



Code N: Non-turnable mast
Code T: Manually turnable mast 360°
Code R: Electric turning base 12/24V

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast

Steady Medium Masts

Light Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CL.6501.N	N	90mm	5	2.643	1.026	20	12.8	150
CL.6502.N	N	90mm	5	3.121	1.146	20	14.0	140
CL.6503.N	N	90mm	5	3.704	1.229	20	14.7	130
CL.6504.N	N	90mm	5	4.371	1.406	18	16.0	140
CL.6505.N	N	90mm	5	4.971	1.546	16	17.2	130
CL.6506.N	N	90mm	5	5.573	1.676	16	18.3	115
CL.6507.N	N	90mm	5	6.331	1.826	14	19.6	130
CL.6508.N	N	90mm	5	7.151	2.006	12	21.1	120
CL.6509.N	N	90mm	5	7.944	2.191	10	22.8	100
CL.6501.T	T	90mm	5	2.68	1.063	20	15.2	150
CL.6502.T	T	90mm	5	3.208	1.183	20	16.3	140
CL.6503.T	T	90mm	5	3.741	1.266	20	17.0	130
CL.6504.T	T	90mm	5	4.408	1.443	18	18.5	140
CL.6505.T	T	90mm	5	5.008	1.583	16	19.6	130
CL.6506.T	T	90mm	5	5.61	1.713	16	20.6	115
CL.6507.T	T	90mm	5	6.368	1.863	14	22.0	130
CL.6508.T	T	90mm	5	7.188	2.043	12	23.5	120
CL.6509.T	T	90mm	5	7.981	2.228	10	25.2	100



Code N: Non-turnable mast
 Code T: Manually turnable mast 360°
 Code R: Electric turning base 12/24V

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast Steady Medium Masts

Standard Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CS.6431.N	N	115mm	4	2.828	1.199	60	17.5	145
CS.6432.N	N	115mm	4	3.313	1.339	60	18.9	135
CS.6433.N	N	115mm	4	3.92	1.484	60	20.5	125
CS.6434.N	N	115mm	4	4.355	1.604	60	21.7	135
CS.6435.N	N	115mm	4	4.913	1.739	60	23.2	125
CS.6436.N	N	115mm	4	5.363	1.859	50	24.4	115
CS.6437.N	N	115mm	4	5.883	1.989	50	25.9	125
CS.6438.N	N	115mm	4	6.384	2.139	50	27.2	115
CS.6439.N	N	115mm	4	6.885	2.259	45	28.6	110
CS.6431.T	T	115mm	4	2.865	1.236	60	21.6	145
CS.6432.T	T	115mm	4	3.35	1.376	60	23.0	135
CS.6433.T	T	115mm	4	3.957	1.521	60	24.6	125
CS.6434.T	T	115mm	4	4.392	1.641	60	25.8	135
CS.6435.T	T	115mm	4	4.95	1.776	60	27.3	125
CS.6436.T	T	115mm	4	5.4	1.896	50	28.5	115
CS.6437.T	T	115mm	4	5.92	2.026	50	30.0	125
CS.6438.T	T	115mm	4	6.421	2.176	50	31.3	115
CS.6439.T	T	115mm	4	6.922	2.296	45	32.7	110



Code N: Non-turnable mast
Code T: Manually turnable mast 360°
Code R: Electric turning base 12/24V

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast

Steady Medium Masts

Standard Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CS.6516.N	N	115mm	5	4.16	1.406	60	22.0	135
CS.6517.N	N	115mm	5	4.404	1.486	60	22.5	130
CS.6518.N	N	115mm	5	4.872	1.576	60	23.7	125
CS.6519.N	N	115mm	5	5.374	1.666	50	25.0	130
CS.6520.N	N	115mm	5	5.872	1.776	50	26.2	125
CS.6521.N	N	115mm	5	6.372	1.876	50	27.5	115
CS.6522.N	N	115mm	5	6.852	1.976	45	28.7	125
CS.6523.N	N	115mm	5	7.872	2.196	40	31.3	115
CS.6524.N	N	115mm	5	8.874	2.406	40	34.0	100
CS.6516.T	T	115mm	5	4.197	1.443	60	26.0	135
CS.6517.T	T	115mm	5	4.441	1.523	60	26.6	130
CS.6518.T	T	115mm	5	4.909	1.613	60	27.8	125
CS.6519.T	T	115mm	5	5.411	1.703	50	29.0	130
CS.6520.T	T	115mm	5	5.909	1.813	50	30.3	125
CS.6521.T	T	115mm	5	6.409	1.913	50	31.5	115
CS.6522.T	T	115mm	5	6.889	2.013	45	32.8	125
CS.6523.T	T	115mm	5	7.909	2.233	40	35.5	115
CS.6524.T	T	115mm	5	8.911	2.443	40	38.0	100



Code N: Non-turnable mast
Code T: Manually turnable mast 360°
Code R: Electric turning base 12/24V

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast Steady Medium Masts

Standard Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CS.6601.N	N	115mm	6	3.647	1.233	45	21.0	140
CS.6602.N	N	115mm	6	4.209	1.333	45	22.4	135
CS.6603.N	N	115mm	6	5.047	1.483	45	24.3	120
CS.6604.N	N	115mm	6	5.847	1.643	45	26.2	120
CS.6605.N	N	115mm	6	6.887	1.818	45	28.7	105
CS.6606.N	N	115mm	6	7.987	2.018	40	31.3	105
CS.6607.N	N	115mm	6	9.186	2.218	40	34.0	90
CS.6608.N	N	115mm	6	10.227	2.408	35	36.5	150
CS.6609.N	N	115mm	6	10.932	2.533	35	38.2	140
CS.6601.T	T	115mm	6	3.684	1.27	45	25.1	140
CS.6602.T	T	115mm	6	4.246	1.37	45	26.5	135
CS.6603.T	T	115mm	6	5.084	1.52	45	28.5	120
CS.6604.T	T	115mm	6	5.884	1.68	45	30.3	120
CS.6605.T	T	115mm	6	6.924	1.855	45	32.8	105
CS.6606.T	T	115mm	6	8.024	2.055	40	35.4	105
CS.6607.T	T	115mm	6	9.223	2.255	40	38.2	90
CS.6608.T	T	115mm	6	10.264	2.445	35	40.6	150
CS.6609.T	T	115mm	6	10.969	2.57	35	42.3	140



Code N: Non-turnable mast
Code T: Manually turnable mast 360°
Code R: Electric turning base 12/24V

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast Steady Medium Masts

Standard Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CS.6701.N	N	115mm	7	3.377	1.17	40	20.7	130
CS.6702.N	N	115mm	7	4.193	1.29	40	22.7	120
CS.6703.N	N	115mm	7	4.997	1.41	35	24.4	115
CS.6704.N	N	115mm	7	5.654	1.515	35	25.8	110
CS.6705.N	N	115mm	7	6.357	1.63	30	27.4	120
CS.6706.N	N	115mm	7	7.155	1.748	30	29.0	110
CS.6707.N	N	115mm	7	7.958	1.881	30	30.8	95
CS.6708.N	N	115mm	7	9.155	2.07	30	33.4	80
CS.6709.N	N	115mm	7	10.357	2.24	30	36.0	140
CS.6701.T	T	115mm	7	3.414	1.207	40	25.0	130
CS.6702.T	T	115mm	7	4.23	1.327	40	26.8	120
CS.6703.T	T	115mm	7	5.034	1.447	35	28.5	115
CS.6704.T	T	115mm	7	5.691	1.552	35	30.0	110
CS.6705.T	T	115mm	7	6.394	1.667	30	31.5	120
CS.6706.T	T	115mm	7	7.192	1.787	30	33.2	110
CS.6707.T	T	115mm	7	7.995	1.918	30	35.0	95
CS.6708.T	T	115mm	7	9.192	2.107	30	37.5	80
CS.6709.T	T	115mm	7	10.394	2.277	30	40.1	140



Code N: Non-turnable mast
Code T: Manually turnable mast 360°
Code R: Electric turning base 12/24V

* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information