

Fireco masts

Pneumatic mast Steady Small Masts

Ultralight Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CU.6316.N	N	77mm	3	2.253	1.085	25	9.0	150
CU.6317.N	N	77mm	3	2.7	1.25	25	10.0	140
CU.6318.N	N	77mm	3	3.126	1.384	25	10.5	130
CU.6319.N	N	77mm	3	3.617	1.555	25	11.5	145
CU.6320.N	N	77mm	3	4.117	1.725	25	12.5	135
CU.6321.N	N	77mm	3	4.595	1.895	22	13.0	125
CU.6322.N	N	77mm	3	5.117	2.065	20	14.0	160
CU.6323.N	N	77mm	3	5.599	2.235	20	15.0	150
CU.6324.N	N	77mm	3	6.067	2.405	18	16.0	140
CU.6316.T	T	77mm	3	2.297	1.129	25	10.5	150
CU.6317.T	T	77mm	3	2.744	1.294	25	11.5	140
CU.6318.T	T	77mm	3	3.17	1.428	25	12.0	130
CU.6319.T	T	77mm	3	3.661	1.599	25	13.0	145
CU.6320.T	T	77mm	3	4.161	1.769	25	14.0	135
CU.6321.T	T	77mm	3	4.639	1.939	22	14.5	125
CU.6322.T	T	77mm	3	5.161	2.109	20	15.5	160
CU.6323.T	T	77mm	3	5.643	2.279	20	16.5	150
CU.6324.T	T	77mm	3	6.111	2.449	18	17.5	140



* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information

Fireco masts

Pneumatic mast Steady Small Masts

Ultralight Steady - with internal cable

P/N	Code	Diameter	Sections	Ext. Height (m)	Ret. Height (m)	Max. load (kg)	Weight (kg)	Max. wind km/h
CU.6401.N	N	77mm	4	2.441	1.024	20	10.0	160
CU.6402.N	N	77mm	4	2.944	1.172	20	10.8	150
CU.6403.N	N	77mm	4	3.424	1.292	20	11.5	140
CU.6404.N	N	77mm	4	3.932	1.422	20	12.3	150
CU.6405.N	N	77mm	4	4.597	1.592	16	13.4	135
CU.6406.N	N	77mm	4	5.274	1.762	16	14.5	120
CU.6407.N	N	77mm	4	5.873	1.932	13	15.5	130
CU.6408.N	N	77mm	4	6.422	2.122	13	16.5	115
CU.6409.N	N	77mm	4	6.962	2.292	12	17.5	105
CU.6401.T	T	77mm	4	2.485	1.068	20	11.5	160
CU.6402.T	T	77mm	4	2.988	1.216	20	12.3	150
CU.6403.T	T	77mm	4	3.468	1.336	20	13.0	140
CU.6404.T	T	77mm	4	3.976	1.466	20	13.8	150
CU.6405.T	T	77mm	4	4.641	1.636	16	14.8	135
CU.6406.T	T	77mm	4	5.318	1.806	16	16.0	120
CU.6407.T	T	77mm	4	5.917	1.976	13	16.9	130
CU.6408.T	T	77mm	4	6.466	2.166	13	18.0	115
CU.6409.T	T	77mm	4	7.006	2.336	12	18.9	105



* denotes 1 level guy lines required, fitted to top section. ** denotes 2 levels of guy rings/lines required. *** denotes 3 levels of guy rings/lines required - consult ZCG for more information