

ZN2-675-06

UHF CB Radio 477MHz Mast Mount Collinear

The ZN2-675-06 mast mount collinear is specifically designed and manufactured for UHF CB Radio communications at the 477MHz frequency.

The ZN2-675-06 has foam filled internals to improve longevity of the antenna in the harsh Australian environment.

Mountin accessories, coaxial feeder cable, water-proofing and other installation accessories are all available separately.

Specifications	ZN2-675-06
Construction	White fibreglass radome, anodised aluminium mount section - foam filled
Frequency range	UHF CB Radio 477MHz
VSWR	<1.5:1
Tuning	Factory
Gain	6 dBi
Maximum power	100 Watts
Impedance	50 Ohm
Polarisation	Vertical
H Plane	360° omnidirectional
Connector - fitted	UHF female in base of mount section
Mount section	340mm x 20mm anodised aluminium
Height	1.85 metres
Weight	700grams
Mounting hardware (order separate)	Mast mounting: 2 x EB1-SS or 1 x UB3-SS Side/wall mounting: 2 x NSM-B20M
Mounting position (recommended)	Mount as high on your structure, mast or tower as possible using the appropriate mounting clamp/s

Lower gain model available	
ZN2-375-03	4.5dBi - 1.65 metres



EB1-SS



UB3-SS



NSM-B20M