

Dummy loads

N-type male plug terminated

50 Ohm, Up to 3GHz



In-stock
Ready to
Ship
* Signifies build to
order item

The purpose of a dummy load (also known as a termination load) is to absorb energy and convert it into heat. The dummy loads takes the place of an antenna during transmitter testing and adjustment.

Other applications where dummy loads are used include, hybrid couplers, isolators, circulators, system testing, calibration and filtering and multicoupling.

Filters, combiners, hybrid couplers, antennas and other installation accessories are all available separately.

	8258-9*	8258-4	8258-2	8259	8260	8258-3*
Construction	Tri-metal plated	Black passivated aluminium heatsink and chrome plated termination				
Heatsink size	-	Medium	Large			
Maximum power	1 Watt	2 Watts	5 Watts	25 Watts	60 Watts	200 Watts
Connector	N-type male plug interface					
Frequency	DC~3GHz	DC~6GHz	DC~3GHz			
VSWR	<1.2:1					<1.25:1
Impedance	50 Ohms					
Operating temperature	-40°C to +85°C					-55°C to +125°C
Storage temperature	-40°C to +80°C					-60°C to +135°C
Dimensions	Length: 30mm Diameter: 20mm	Length: 32mm Diameter: 15mm	Length: 36mm Diameter: 20mm	Length: 83mm Width: 60mm Height: 61mm	Length: 124mm Width: 60mm Height: 60mm	Length: 226mm Width: 142mm Height: 64mm
Weight	34grams	40grams	40grams	300grams	400grams	1.85kg
Waterproof rating	-	-	-	-	-	IP66



Dummy loads

7/16" DIN male terminated

50 Ohm, Up to 3GHz



The purpose of a dummy load (also known as a termination load) is to absorb energy and convert it into heat. The dummy loads takes the place of an antenna during transmitter testing and adjustment.

Other applications where dummy loads are used include, hybrid couplers, isolators, circulators, system testing, calibration and filtering and multicoupling.

Filters, combiners, hybrid couplers, antennas and other installation accessories are all available separately.

	8258-5*	8258-6*	8258-7*
Construction	Black passivated aluminium heatsink and chrome plated termination		
Heatsink size	Small	Large	
Maximum power	30 Watts	50 Watts	100 Watts
Connector	7/16" DIN male		
Frequency range	DC to 3GHz		
VSWR	<1.2:1		
Impedance	50 Ohms		
Operating temperature	-40°C to +85°C		
Storage temperature	-40°C to +85°C		
Dimensions	Length: 36mm Diameter: 20mm	Length: 83mm Width: 60mm Height: 61mm	Length: 124mm Width: 60mm Height: 60mm
Weight	40grams	300grams	400grams
Waterproof rating	-	-	-

