



ZW312B AM/FM series

5/16"-26 brass or 3/8"-24 TPI threaded whips

AM/FM radio receive only



The ZW312B black whips are an effective receive whip designed for receive purposes for both AM and FM Radio. The ZW312B and ZW312B-BLK come standard with a female 5/16"-26 brass thread in the mount ferrule.

The ZW312B-EUR has a 3/8"UNF-24 TPI thread at the base.

Mounting hardware, bird-proofing and other installation accessories are all available separately.

	ZW312B-BLK	ZW312B	ZW312B-EUR
Colour	Black	White	Black
Construction	Heatshrunk braided fibreglass and chrome mount ferrule		
Frequency range	AM radio 530-1600kHz and FM radio 87.5-108MHz		
Gain	Receive only		
Tuning	Factory		
Maximum power	Receive only		
Polarisation	Vertical		
H Plane	360° omnidirectional ± 0.5 dBd - Receive only		
Height	640mm		
Weight	60grams		
Mount ferrule thread	5/16"-26 brass female thread		European 3/8" UNF-24 TPI male thread
Mounting hardware order separate	Base: OB base Cable base: CRBL with radio connector Magnetic base: MGB-OB and specify radio connector		Consult ZCG - requires a female 3/8" UNF - 24 TPI base
Mounting position recommended	Mount as high on your vehicle or structure as possible using an appropriate base, bracket or magnetic base.		
Alternate models with base incl.	ZM312B-BK - all black whip and base	ZM312B - all white whip and base	-

