

## GID-MB4052B-S

### All-black broadband ground independent elevated feed whip 400-520 MHz



The GID-MB4052B-S ground independent broadband UHF or Land Mobile Radio (L.M.R.) antenna is suitable for installations where reduced height is required. Ideal for emergency services or multi-channel UHF comms requirements.

Mounting hardware, adaptors, connectors and other installation accessories are all available separately.


Construction	All-black whip, elevated feed assembly, parallel spring base and coaxial cable
Frequency range	400-520MHz - UHF, LMR, GRN compatible
Bandwidth	Full frequency range stated - 120 MHz
VSWR	<1.5:1
Tuning	Factory
Gain	2.1dBi
Maximum power	50 Watts
Ground independent	Yes
Impedance	50 Ohms
Polarisation	Vertical
H Plane	360° omnidirectional
Cable	5 metres black RG58A/U stranded - bottom exit from spring base
Connector	UHF male PL259 supplied not fitted or specify requirements
Height	440mm including spring
Weight	700grams
Mounting hardware order separate	Mount using the parallel spring onto an appropriate 16mm hole bracket such as BBM-SS bull bar mount or BBKB-B knock-down mount, or alternatively utilise any 16mm hole.
Mounting position recommended	As high on your vehicle/structure as possible using an appropriate bracket or mount hole. Mount antenna minimum 350mm away from any other antenna.
Installation tools required	21mm spanner for base nut securing




PL259 UHF male  
supplied not fitted

## GID-MB4052B-S

All-black broadband ground independent elevated feed whip  
400-520 MHz



Example radiation pattern



## GID-MB4052B-S

All-black broadband ground independent elevated feed whip  
400-520 MHz


### Recommended installation accessories

 <p><b>SKU: BBM-SS</b> Wrap around bull bar mount, up to 50mm diameter bull bar tube 16mm mount hole Requires 10mm spanner</p>	 <p><b>SKU: BBMXL-SS</b> Wrap around extra large bull bar mount, up to 76mm diameter bull bar tube 16mm mount hole Requires 10mm spanner</p>
 <p><b>SKU: MRM-SS</b> 304 stainless steel 'Mirror mount' clamp bracket 16mm mount hole Requires 10mm spanner</p>	 <p><b>SKU: BBKB-B</b> Knock-down antenna mount, powder coated black 16mm mount hole with 5.5mm cable hole</p>
 <p><b>SKU: ATLM-B</b> Adjustable bonnet, boot and door jam mount. 360 rotational and 140 degree adjustment 16mm mount hole Includes 5mm and 2mm allen keys</p>	 <p><b>SKU: GM1</b> 304 stainless steel 'L' mount bracket 16mm mount hole</p>
 <p><b>SKU: GM2</b> 304 stainless steel 'Z' mount bracket 16mm mount hole</p>	
 <p><b>SKU: A-2845</b> Powdercoated black tri-magnetic mount base 13mm hole Santoprene coated magnets for scratch reduction</p>	 <p><b>SKU: MGB</b> Powdercoated black internal magnet mount base 16mm hole 105mm diameter includes scratch reduction pad on base</p>

## GID-MB4052B-S

All-black broadband ground independent elevated feed whip  
400-520 MHz

Vehicle Mounting locations



- Best/Recommended location for mounting
- Suitable mounting locations
- Not suitable mounting locations