



SGDB-TPM series

Mobile phone/wireless data improvement

All networks dualband 4G 825-960 MHz & 1710-2190 MHz



At some remote locations, inside a building or whilst travelling, mobile phone and wireless data reception can often be poor, the SGDB-TPM is an adaptable antenna for mounting outdoors at your home or office.

Please note: the SGDB-TPM series will not transmit/receive signal where no cellular infrastructure is present, please check network coverage.

Mounting hardware, adaptors, bird-proofing and other installation accessories are all available separately.

SKU	SGDB-B-TPM - black radome	SGDB-W-TPM* - white radome
Construction	Black fibreglass radome, black anodised aluminium mount ferrule, external cable assembly and termination	White fibreglass radome, clear anodised aluminium mount ferrule, external cable assembly and termination
Frequency range	825-960 MHz & 1710-2190 MHz - all networks dualband 4G, including ISM 900 MHz	
Bandwidth	Full frequency ranges stated	
VSWR	Average: <1.6:1, Maximum <3:1 VSWR	
Tuning	Factory	
Gain	6.2 dBi at 825-960 MHz and 3 dBi at 1710-2190 MHz	
Maximum power	30 Watts	
Impedance	50 Ohms	
Polarisation	Vertical	
H Plane	360° omnidirectional ± 0.5 dBd	
E Plane	32°	
Cable	5 metres RG58 low loss, solid core - side exit from ferrule	
Connector	FME female fitted to cable as standard or specify requirements	
Height	800mm	
Weight	700grams	
Mounting hardware order separate	See following pages for suitable mount hardware or any minimum 13mm hole	
Mounting position recommended	As high on your structure/tower or building as possible, using the appropriate mounting hardware.	



Threaded ferrule mount with side exit cable



FME female fitted as standard or specify requirements




SGDB-TPM series


Mobile phone/wireless data improvement

All networks dualband 4G 825-960 MHz & 1710-2190 MHz

**In-stock
Ready to
Ship**
* Signifies build to
order item



Example radiation pattern




Mtr	Ref	Delta	Ref Freq	Ref Amp	Delta Freq	Delta Amp
1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	825.246 MHz	1.46VSWR	--	--
2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	892.500 MHz	1.13VSWR	--	--
3	<input checked="" type="checkbox"/>	<input type="checkbox"/>	959.755 MHz	1.77VSWR	--	--
4	<input type="checkbox"/>	<input type="checkbox"/>	--	--	--	--

Typical VSWR - 825-960 MHz


SGDB-TPM series

Mobile phone/wireless data improvement


All networks dualband 4G 825-960 MHz & 1710-2190 MHz



SKU: A-4266
Clear anodised aluminium
mast mount adaptor
Requires 2 x EB1-SS, 1 x UB3-SS
or 2 x RB8 or 1 x UB2-SS
Can be used with CFB series or
A-2654-2



SKU: GM1
304 stainless steel 'L' fascia
mount bracket
16mm hole
Requires mounting screws/
bolts - not supplied



SKU: A-6211
304 stainless steel 'L' fascia
mount bracket
16mm hole, 200mm offset
Requires mounting screws/
bolts - not supplied




SKU: MGB
Powdercoated black internal
magnet mount base
16mm hole
105mm diameter
includes scratch reduction pad
on base



SKU: CFB****
Galvanised steel 'J' hockey stick
brackets, 1.1 - 2.1 metres.

Requires A-4266 series + 2 x
EB1-SS or 1 x UB2-SS



SKU: A-2654-2
Aluminium pole extension 1.1
metres includes pole mounting
brackets.

Requires A-4266 + 2 x EB1-SS
or 1 x UB2-SS



Alternate Spring base
SKU: A-1269
'Barrel' stainless steel spring
base with 1/2" bolt and spring
washer

Requires 19mm spanner



Alternate Spring base
SKU: A-1270
Parallel heavy-duty mount
spring, includes base mount
bolt

Requires 19mm spanner



Alternate Spring base
A-1269-12
'Barrel' stainless steel spring
base with threaded stud and
split nut

Requires 19mm spanner



Alternate Spring base
A-1269-14
'Barrel' stainless steel spring
base with 50mm base
extension. Suitable for behind
bull bar mounting or wing
mirror bracket mounting


Requires 19mm spanner

Typical alternate connectors



SKU: SM-7963-7
SMA male termination
Suits mobile/telemetry devices.

Also available in right-angle
configuration, alternate gender
or reverse polarity



SKU: NM-7933-2
N-type male termination
Suits mobile/telemetry devices

Also available in right-angle
configuration or alternate
gender