



4266 SG series mast mount adaptor

Converts vehicle mounted antenna to mast mount capability



If a vehicle mount antenna requires modification to a fixed position configuration usage, ZCG can supply a A-4266 series mast mount adaptor suitable for SG series antenna for mounting onto an external pole, tripod or wall mounting.

Antennas, coaxial feeder cable, water-proofing, mounting hardware and other installation accessories are all available separately.

	A-4266	A-4266-2	A-4266-4*	A-4266-5*	A-4266-8*	A-4266-3*
Construction	CNC lathed corrosion resistant aluminium					CNC lathed 304 stainless steel
Length	150mm			2.0m	150mm	
Diameter	25mm O.D.				30mm O.D.	25mm O.D.
Thread	Top: 1/2"-12 BSW	Top: 1/2"-12 BSW Bottom: 8mm hole through middle	Top: 1/2"-12 BSW female Bottom: 1/2"-12 BSW female	Top: 1/2"-12 BSW female	Top: 1/2"-12 BSW female Bottom: 1/4"-20UNC female	Top: M12 x 1.75 female
Suitable antennas	All SG series antennas, excluding SGL series	Any bottom exit SG series with no connector	All SG series antennas, excluding SGL series	All SG series requiring extended mounting	Suitable for small tripod mounting	SGDB-SS-S series or any M12 x 1.75 male thread
Installation requirements	<p>If spring base present, remove spring base and attach mast mount adaptor using thread. Ensure mast mount adaptor is tightly attached up to the bottom face of the mount ferrule. Some loctite may be applied for long term attachment. The mast mount adaptor will require mounting clamp/s, see below.</p> <p><u>Alternatively ZCG can fit any A-4266 series onto your SG series during manufacture for ease of installation.</u></p>					
Mounting hardware order separate	<p>Parallel: 2 x EB1-SS or 1 x UB3-SS Right-angle: 2 x RB8, 2 x RB8-L or 1 x UB2-SS</p> <p>Alternative: For the A-4266-4, utilising the spring base bolt mounting into a 12.7mm hole or bracket.</p> <p>Alternative: A-4266-4-B model includes 1/2"-12 BSW bolt for SG-TPM series without spring bases and bolts</p>					



ZCG recommended mounting arrangement on following page...



4266 SG series mast mount adaptor

Converts vehicle mounted antenna to mast mount capability


In-stock
Ready to
Ship
*Build to order
item

A-4266 Series Fitment Guide



STEP 1: Unscrew spring base from antenna mounting ferrule



STEP 2: Screw your A-4266 series adaptor onto your mount ferrule thread - side exit cable models only



STEP 3: Screw your A-4266 series adaptor onto your ferrule until flush - loctite can be applied for long term installations



STEP 4: Install your mounting hardware onto your A-4266 series adaptor - example used RB8-L, will require 2 RB8-L for secure mounting.



Alternatively: For A-4266-4 adaptors only, you can mount using the spring base bolt in the bottom 1/2"-12BSW thread into a 12.7mm hole or suitable bracket. If antenna didn't have spring base such as SGDB-TPM please purchase a A-4266-4-B which includes a 1/2"-12BSW bolt with spring washer.

A-4266-2 Fitment Guide



STEP 1: This is for bottom exit cable SG series antennas only such as SGDB-TPM-BE. Remove connector if terminated.



STEP 2: Insert cable into the A-4266-2 adaptor and push through



STEP 3: Screw your A-4266-2 adaptor onto your ferrule until flush - loctite can be applied for long term installations



STEP 4: Install your mounting hardware onto your A-4266-4 series adaptor - example used RB8-L, will require 2 RB8-L for secure mounting.