

Bird-proofing

Stainless steel braid

Page 1 of 2



Stainless steel bird-proofing braid is the ideal solution for protection of coaxial cable from damage from birds and other animals, which can result in system failure. Available in either 304 grade or 316 stainless steel depending on your requirements, specify on your order. ZCG's range of stainless steel braid is temperature rated from -40°C to +700°C suitable for Arctic through to desert locations.

ZCG recommend the use of stainless steel cable ties to secure the stainless steel braid - P/N 8117.

ZCG can manufacture any of our antennas with external cable or custom cable assemblies with the stainless steel braid fitted, ready for installation in your location.

Coaxial cable, connectors, water-proofing and other installation accessories are all available separately.

A-7860 - 304 grade

Order code - per metre	7860
Sizing	6mm I.D. - suits RG58, RG58LL, RG59 or RG142

A-7860-1* - 304 grade

Order code - per metre	7860-1
Sizing	3mm I.D. suits RG174A/U or RG316

A-7860-2 - 304 grade

Order code - per metre	7860-2
Sizing	10mm I.D. - suits RG213, RG214, RU400 or ZCG1450

A-7860-3 - 304 grade

Order code - per metre	7860-3
Sizing	20mm I.D.

A-7860-4 - 304 grade

Order code - per metre	7860-4
Sizing	32mm I.D. - suits 7/8" ZCG7850



Bird-proofing

Stainless steel braid

Page 2 of 2


In-stock
Ready to
Ship
* Signifies build to
order item

A-7860-5* - 304 grade

Order code - per metre	7860-5
Sizing	38mm I.D.

A-7860-6* - 304 grade

Order code - per metre	7860-6
Sizing	50mm I.D. - suits 1-5/8" ZCG1580

A-7860-7* - 304 grade

Order code - per metre	7860-7
Sizing	25mm I.D.

A-7860-8 - 304 grade

Order code - per metre	7860-8
Sizing	12mm I.D.

A-7860-9* - 304 grade

Order code - per metre	7860-9
Sizing	16mm I.D. suits 1/2" ZCG1250 & ZCG1250SF

A-7860-10* - 304 grade

Order code - per metre	7860-10
Sizing	59.3mm I.D.

A-7860-11* - 316 grade

Order code - per metre	7860-12
Sizing	16mm I.D. suits 1/2" ZCG1250 & ZCG1250SF

A-7860-12* - 316 grade

Order code - per metre	7860-12
Sizing	38mm I.D.

