



## ZCG1250SF

1/2" super flexible foam dielectric  
50 Ohm coaxial cable

 In-stock  
Ready to  
Ship

The Specifications and attenuation performance of our 1/2" super flexible, foam dielectric, 50 Ohm coaxial cable are comparable with any other brand available.

This coaxial cable is available in metre cut lengths or by the roll, please consult ZCG for more information.



### 1/2" super flexible coaxial cable ZCG1250SF

Order code - per metre	ZCG1250SF
Order code 500m roll	ZCG1250SF-500
Centre conductor	Copper-clad aluminium wire, 3.60mm
Dielectric	Physical foam polyethylene (PE), 9.10mm
Outer conductor	Helical copper tube, 12.0mm
Jacket	Black polyethylene (PE), 13.3mm outside diameter - low smoke halogen-free fire retardant available

### Mechanical specifications

Minimum bend radius	Single: 15mm	Repeated: 30mm
Weight	20Kg per 100 metres	
Operating temperature	-55°C to +85°C	

### Electric specifications

Impedance	50 Ohm
Nominal capacitance	80.0 pF/m
Velocity of propagation	82%
RF peak voltage	1.13kV
Peak power rating	19kW
Shielding effectiveness	>10MHz >120dB
Insulation resistance	5000MΩ km
Maximum frequency	DC~12.5GHz

Attenuation figures on following page...





## ZCG1250SF

1/2" super flexible foam dielectric  
50 Ohm coaxial cable

  
In-stock  
Ready to  
Ship

Attenuation	Per 100 metres	Maximum power
100MHz	3.22dB	3.03kW
150MHz	4.05dB	2.39kW
200MHz	4.65dB	2.11kW
280MHz	5.65dB	1.69kW
450MHz	7.20dB	1.37kW
800MHz	9.86dB	1.00kW
900MHz	10.56dB	0.94kW
1000MHz	11.15dB	0.88kW
1500MHz	13.80dB	0.70kW
1800MHz	15.55dB	0.63kW
2000MHz	16.40dB	0.59kW
2200MHz	17.35dB	0.56kW
2400MHz	18.10dB	0.53kW
2500MHz	18.50dB	0.52kW
3000MHz	20.90dB	0.48kW

