

ZCG1450SF

1/4" super flexible foam dielectric 50 Ohm coaxial cable

Our 1/4" super flexible foam dielectric, 50 Ohm coaxial cable has specifications and attenuation performance to match or surpass all other brands on the market.

This coaxial cable is available in metre cut lengths, please consult ZCG for more information.

Specifications	1/4" super flexible coaxial cable ZCG1450SF	
Order code - per metre	ZCG1450SF	
Centre conductor	Copper-clad aluminium wire, 1.90mm	
Dielectric	Physical foam polyethylene (PE), 4.75mm	
Outer conductor	Helical copper tube, 6.35mm	
Jacket	Black polyethylene (PE), 7.50mm outside diameter	
Mechanical specifications		
Minimum bend radius	Single: 12.5mm	Repeated: 25.0mm
Weight	46Kg per 100 metres	
Operating temperature	-55°C to +85°C	
Electric specifications		
Impedance	50 Ohm	
Nominal capacitance	80.0 pF/m - 24.4pF/ft	
Velocity of propagation	83%	
RF peak voltage	0.80kV	
Peak power rating	6.40kW	
Shielding effectiveness	>120dB	
Insulation resistance	5000MΩ km	
VSWR	800MHz - 1GHz = <1.15 1.7GHz - 2.2GHz = <1.15 2.2GHz - 2.7GHz = <1.15	
Cut-off frequency	20.40GHz	



Attenuation figures on following page...

ZCG1450

1/4" super flexible foam dielectric
50 Ohm coaxial cable



Attenuation	Per 100 metres	Maximum power
100MHz	5.60dB	1.23kW
150MHz	7.25dB	0.95kW
200MHz	8.00dB	0.86kW
280MHz	10.20dB	0.67kW
450MHz	12.20dB	0.57kW
800MHz	16.70dB	0.42kW
900MHz	17.50dB	0.39kW
1000MHz	18.60dB	0.37kW
1500MHz	23.40dB	0.30kW
1800MHz	25.70dB	0.27kW
2000MHz	26.90dB	0.26kW
2200MHz	28.50dB	0.25kW
2400MHz	30.00dB	0.24kW
2500MHz	30.60dB	0.23kW
3000MHz	33.50dB	0.21kW

