



75 Ohm connectors

N-type, BNC & F-type

7962-2




BNC female flange mount connector




C = 4.0 mm

7962-3




BNC female bulkhead mount connector




C = 4.0 mm

7978-2




BNC male crimp connector For RG59 cable




A = 13.0 mm
C = 3.0 mm

7978-3




BNC male crimp connector For RG11 cable



A = 14.0 mm
C = 2.5 mm

8267




BNC male solder pin clamp style connector For RU400-75 cable

Tri-metal plated Low P.I.M.




A = 10.0 mm
B = 5.0 mm
C = 5.0 mm

8289-1




F-type male crimp connector For RG59/RG6 cable




A = 10.0 mm
B = 5.0 mm
C = 4.0 mm

8261




N-type female crimp connector For RG59 cable




A = 13.0 mm
C = 2.5 mm

8262




N-type female crimp connector For RG6 cable




A = 13.0 mm
C = 2.5 mm

8263




N-type female crimp connector For RG11 cable




A = 13.0 mm
C = 3.0 mm

8266



N-type male solder pin clamp style connector For RU400-75 cable

Tri-metal plated Low P.I.M.



A = 10.0 mm
B = 5.0 mm
C = 4.0 mm

8257



Pin for 8261 or 8263 N-type female crimp connector For RG59/RG11 cable

8257-2



Pin for 8262 N-type female crimp connector For RG6 cable