

EIA flange connectors 1/2", 7/8" or 1-5/8" cable

EIA Connectors are ideal for high power transmission installation with metal to metal contact between cable and connector. No plastic components are used.

To join two cables with EIA connectors, two identical flange sockets are fitted to the cables to be joined. A capitivated joining bullet is used to make a quick, easy and solderless connection between the two EIA flange conductors.

Coaxial feeder cable, bird proofing and water-proofing and other installation accessories are all available separately.



Specifications	78EIA1250	78EIA7850	158EIA15850
Cable type	1/2" foam dielectric or radiating cable	7/8" foam dielectric or radiating cable	1-5/8" foam dielectric or radiating cable
Mating interface	7/8" EIA	7/8" EIA	1-5/8" EIA
Maximum frequency	3.7GHz	3.7GHz	3.7GHz
Connector plating	Silver	Silver	Silver
Outer diameter	57mm	57mm	87mm
Length	85mm	76.5mm	120mm
Weight	280grams	380grams	1.14Kg
Joining kit contents (supplied)	1 x Joining bullet 2 x O-rings 3 x Bolts & nuts 6 x Washers	1 x Joining bullet 2 x O-rings 3 x Bolts & nuts 6 x Washers	1 x Joining bullet 2 x O-rings 4 x Bolts & nuts 8 x Washers