



SMA, SMB & SMC connectors

Page 1 of 3

7901



SMA male crimp connector
For RG174/RG316 cable

A = 12.0 mm
B = 5.0 mm
C = 3.0 mm

7901-3



SMA male crimp connector
For RG174/RG316 cable

A = 10.0 mm
B = 4.5 mm
C = 2.0 mm

7963-3



Right-angle SMA male connector, crimp sleeve with solder pin
For RG58 cable

A = 14.0 mm
C = 3.0 mm

7963-4

Reverse SMA male crimp connector
For RG58 cable

A = 13.0 mm
B = 5.5 mm
C = 2.5 mm

7963-7

SMA male crimp connector
For RG58/RG223 cable




A = 11.0 mm
B = 5.0 mm
C = 3.0 mm

7963-8

SMA male right-angle crimp connector
For RG316/RG174 cable




A = For strip dimensions
B = dimensions
C = consult ZCG

7963-10



Reverse SMA male crimp connector
For RG174 cable




A = 12.1 mm
B = 5.1 mm
C = 3.3 mm

7963-13



SMA male right-angle crimp connector
For RG316/RG118/
RG174 cable

A = 12.6 mm
B = 5.8 mm
C = 2.5 mm

7963-14



SMA male right-angle crimp connector
For RG179 cable

A = For strip dimensions
B = dimensions
C = consult ZCG

8204



SMA male crimp connector
RG142 cable
sucoplated

For strip dimensions consult ZCG

8225



SMA male crimp connector
For RG178 cable
Tri-metal plated
Low P.I.M.

For strip dimensions consult ZCG

8277

Right-angle SMA male crimp connector
For RG178/RG316 cable
Gold plated

For strip dimensions consult ZCG

8313

SMA male crimp connector
For RU400 cable






A = 11.0 mm
FOLD BRAID BACK
B = 4.25 mm

SMA, SMB & SMC connectors

Page 2 of 3

7901-2



SMA female bulkhead crimp connector
For RG174/RG316 cable

A = 11.0 mm
B = 5.0 mm
C = 3.0 mm

7901-4



SMA female bulkhead crimp connector
For RG178 cable

A = 11.0 mm
B = 5.0 mm
C = 3.0 mm

7901-5



SMA female crimp connector
For RG174/RG316 cable

A = 11.0 mm
B = 5.0 mm
C = 3.0 mm

7901-6



SMA female bulkhead crimp connector
For RG179 cable

A = For strip
B = dimensions
C = consult ZCG

7901-7



SMA female reverse polarity bulkhead crimp connector
For RG316/RG174 cable

A = For strip
B = dimensions
C = consult ZCG

7950



SMA female panel mount solder connector

C = 4.0 mm

7963-2



SMA female crimp connector
For RG58 cable

A = 13.0 mm
B = 5.5 mm
C = 2.5 mm

8205



SMA female panel mount solder connector
suo-plated

A = 13.0 mm
B = 5.5 mm
C = 2.5 mm

8225-2



SMA female bulkhead crimp connector
For RG178 cable

For strip dimensions consult ZCG

8268



Reverse SMA female crimp connector
For RG58 cable

A = 13.0 mm
B = 5.5 mm
C = 2.5 mm

8313-2

SMA female crimp connector
For RU400 cable


A = 11.0 mm
FOLD BRAID BACK
B = 4.25 mm

SMB connectors on the following page.


SMA, SMB & SMC connectors

Page 3 of 3

8279




SMB male crimp connector
For RG174/RG316 cable




A = 11.1 mm
B = 4.5 mm
C = 2.5 mm

8279-2




SMB female crimp connector
For RG174/RG316 cable




A = For strip dimensions
B = For strip dimensions
C = consult ZCG

8279-3




SMB male right-angle crimp connector
For RG179 cable




A = For strip dimensions
B = For strip dimensions
C = consult ZCG

8296




SMC male crimp connector
For RG174/RG316 cable




For strip dimensions
consult ZCG

8304



SMC reverse male crimp connector
For RG174/RG316 cable



A = 11.1 mm
B = 4.5 mm
C = 2.5 mm

8304-2



Reverse SMC female crimp connector
For RG174/RG316 cable



A = 13.0 mm
B = 5.5 mm
C = 2.5 mm