



TNC connectors 50 Ohms

7902



Reverse TNC male crimp connector
For RG58 cable

A = 15.5 mm
B = 6.5 mm
C = 3.5 mm

7922

TNC male solder clamp style connector
For RG58 cable

A = 8.5 mm
C = 4.0 mm

7930-5



TNC male crimp connector
For RU400/RG8 cable




A = 15 mm
C = 5.0 mm

7943



TNC male crimp connector with solder pin
For RG58 cable

A = 15.5 mm
B = 6.5 mm
C = 3.5 mm

7943-2



TNC male crimp connector with solder pin
RG58 cable

A = 15.5 mm
B = 6.5 mm
C = 3.5 mm

7943-3



Black TNC male crimp connector with solder pin
For RG58 cable

A = 15.5 mm
B = 6.5 mm
C = 3.5 mm

7943-4

TNC male crimp connector with crimp pin
For RG58 cable

A = 15.5 mm
B = 6.5 mm
C = 3.5 mm



7983

TNC male connector with M6 thread



8206



TNC male crimp connector sucoplated
For RG58 cable

A = 15.5 mm
B = 6.5 mm
C = 3.5 mm

8224



TNC male crimp connector
For RG174/RG316 cable

A = 17.5 mm
B = 9.5 mm
C = 4.5 mm

8239



Reverse TNC male crimp connector
For RU400 cable

A =
B =
C =

7907-2



TNC female bulkhead mount connector, crimp sleeve with solder pin
For RG58 cable

A = 15.5 mm
B = 6.5 mm
C = 3.5 mm

7930-6



TNC female crimp connector
For RU400 cable

A = 14.0 mm
B = 5.0 mm

7967



TNC female crimp connector
For RG58 cable

A = 15.5 mm
B = 6.5 mm
C = 3.5 mm

8207

TNC female bulkhead mount connector
For RG58 cable

C = 4.0 mm